

WTRVS-8/15 Series Voice Reach Talking Pendant Necklace



WTRVS-8/15 is a small and lightweight Voice Reach Talking Pendant. Compact and easy-to-use, WTRVS-8/15 is designed to provide complete protection anywhere around your home at any time with the simple touch of a button.

WTRVS-8/15 allows immediate post-alarm voice follow up after an emergency call without any delay and effort. With a simple press of a button it can open two-way voice communication channel between you and the Central Monitoring Station. Additionally, users can talk to the Central Monitoring Station right through the pendant like a speaker phone with the built-in microphone and speaker.

WTRVS-8-FS and WTRVS-15-FS also has a built-in fall sensor and will automatically raise an alarm call and activates two-way voice communications when falls have been detected. As an intelligent device, WTRVS-8/15 really ensures that your emergency issue can be handled properly and timely.



- **Raises a alarm call when a fall as been detected (WTRVS-8-FS & WTRVS-15-FS only)**
- **The microphone and speaker inside allow users to talk to the Central Monitoring Station like a speaker phone**
- **Immediate post-alarm voice follow up after an emergency call**
- **Waterproof to IP67**
- **Power-saving feature for Panel (WTRVS-15 & WTRVS-15-FS only)**
- **Compact and easy to use**
- **Worn around the neck as a pendant**
- **Compatible with our Medical Alarm Panels**

WTRVS-8/15 Series Voice Reach Talking Pendant Necklace

Comprehensive Protection at Home

Specifications

WTRVS-8

DECT Frequencies	1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US)
Power Source	3V, CR123A Lithium battery x1
Battery Life	3 years*
Waterproof Standard	IP67
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	Ø 60mm x 24mm

WTRVS-8-FS

DECT Frequencies	1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US)
Power Source	3V, CR123A Lithium battery x1
Battery Life	1.5 years*
Waterproof Standard	IP67
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	Ø 60mm x 24mm

WTRVS-15

DECT Frequencies	1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US)
RF Frequencies	F1 869MHz / 433MHz
Power Source	3V, CR123A Lithium battery x1
Battery Life	2.8 years*
Waterproof Standard	IP67
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	Ø 60mm x 24mm

WTRVS-15-FS

DECT Frequencies	1880MHz-1900MHz (EU) / 1910MHz – 1930MHz (US)
RF Frequencies	F1 869MHz / 433MHz
Power Source	3V, CR123A Lithium battery x1
Battery Life	1.4 years*
Waterproof Standard	IP67
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	Ø 60mm x 24mm

* Note: Actual battery life may vary with product settings, operating environment, and usage.

WTRVS-8/15 Series Voice Reach Talking Pendant Necklace

Comprehensive Protection at Home

Ordering Information

WTRVS-8	Voice Reach Talking Pendant Necklace
WTRVS-8-FS	Voice Reach Talking Pendant Necklace with Fall Detection
WTRVS-15	Voice Reach Talking Pendant Necklace with power-saving feature
WTRVS-15-FS	Voice Reach Talking Pendant Necklace with Fall Detection & power-saving feature



Grey



Red



Blue

**We offer multiple color options to fulfill all user's needs. Please inquire our Sales team for color options.